

```
1 # /etc/bash/bashrc
2
3 # Proceed no further in the case of a non-interactive shell.
4 if [[ $- != *i* ]]; then
5     return
6 fi
7
8 # Disable errexit in case the user enabled it then chose to re-source this file.
9 shopt -u -o errexit
10
11 # Disable completion when the input buffer is empty. Mute STDERR because this
12 # option is only present in the case that bash was built with readline support.
13 shopt -s no_empty_cmd_completion 2>/dev/null &&
14
15 # Append to HISTFILE rather than overwrite upon exiting, per bug #139609. This
16 # option also requires for bash to have been built with readline support.
17 shopt -s histappend
18
19 # Initialise PROMPT_COMMAND as an array, which is permitted as of bash 5.1.
20 PROMPT_COMMAND=()
21
22 # Don't let the user influence the order of sourcing for bash 5.3 or greater.
23 unset -v GLOBSORT
24
25 for _ in /etc/bash/bashrc.d/*; do
26     if [[ $_ == *.@(bash|sh) && -r $_ ]]; then
27         source "$_"
28     fi
29 done
30
31
32 alias dir='ls -ahlP --time-style=long-iso --group-directories-first --color=auto'
33
34 PS1='\[\033[01;31m\]\h \[\033[01;34m\]\w \$ \[\033[00m\]'
35
36
37
38
39 # Use Zellij for shell for all connections
40 #if [[ -z "$ZELLIJ" && -n "$SSH_CONNECTION" && $- == *i* ]]; then
41 #     exec zellij attach --create main
42 #fi
```